



H&H TUBE

A Division of Sunspring America, Inc.

108 Garfield, P.O. Box 455
Vanderbilt, MI 49795
T (989) 983-2800 F (989) 983-4530

August 31, 2009

Dear Customer:

The enclosed Material Safety Data Sheets (MSDS) have been prepared in compliance with the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. Please direct them to the person responsible for health and safety within your organization. Please note that the MSDS contains information regarding toxic chemicals subject to the reporting requirements of Section 313 of EPCRA and 40 CFR part 373.

MSDS are invaluable tools in the hands of health and safety professionals for hazard evaluation in the confines of the workplace. The general public must exercise caution, however, against direct extrapolation of MSDS health hazard data to the community outside the workplace. In these instances, health, safety and environmental professionals should be consulted to interpret MSDS data.

The alloy composition information contained in these MSDS is intended for employee health and safety education, and is not for material specification purposes.

Sincerely,

Cheri Wilhelm
Safety Director

MATERIAL SAFETY DATA SHEET

H&H TUBE
579 Garfield Avenue
P.O. Box 455
Vanderbilt, MI 49795
PH: (989) 983-2800
FX: (989) 983-2501

DATE: July 25, 2009
Revised: June 14, 2002

SECTION I. MATERIAL IDENTIFICATION

Copper/Copper Alloys

See attached alloy composition sheets for alloy presence and percentages of alloying ingredients.

SECTION II. HAZARDOUS INGREDIENTS

Copper/Copper Alloys

	CAS Number		OSHA-PEL 8-HR TWA	ACGIH-TLV 8-HR TWA (1988-89)	ACGIH STEL (1988-89)
Aluminum	(7429-90-5)	(Dust)	15 mg/m ³	10 mg/m ³	n/a
		(Fume)	5 mg/m ³	5 mg/m ³	n/a
Antimony #	(7440-36-0)		0.5 mg/m ³	0.5 mg/m ³	n/a
Arsenic #	(7440-38-2)		0.5 mg/m ³	0.02 mg/m ³	n/a
Beryllium #	(7440-41-7)		0.002 mg/m ³	0.002 mg/m ³	0.005*
Bismuth Telluride	(1340-82-1)	(Dust)	15 mg/m ³	15 mg/m ³	n/a
Boron Oxide	(1303-86-2)	(Dust)	15 mg/m ³	10 mg/m ³	n/a
Cadmium #	(7440-43-9)	(Dust)	0.2 mg/m ³	0.05 mg/m ³	n/a
		(Fume)	0.1 mg/m ³	0.05 mg/m ³	n/a
Calcium Oxide	(1305-78-8)		5 mg/m ³	5 mg/m ³	n/a
Carbonblack	(1333-86-4)		3.5 mg/m ³	n/a	n/a
Chromium #	(7440-47-3)		1 mg/m ³	0.5 mg/m ³	n/a
Cobalt #	(7440-48-4)		0.05 mg/m ³	0.1 mg/m ³	n/a
Copper #	(7440-50-8)	(Dust)	1 mg/m ³	1 mg/m ³	n/a
		(Fume)	0.1 mg/m ³	0.2 mg/m ³	n/a
Iron	(1309-37-1)		10 mg/m ³	5 mg/m ³	n/a
				(As iron oxide fume)	
Lead # (3)	(7439-92-1)		0.05 mg/m ³	0.15 mg/m ³	n/a
Lithium Hydride	(7580-67-8)		0.025 mg/m ³	0.025 mg/m ³	n/a
Manganese #	(7439-96-5)	(Dust)	5 mg/m ³	5 mg/m ³	n/a
		(Fume)	n/a	1 mg/m ³	3 mg/m ³
Magnesium Oxide	(1309-48-4)	(Dust)	15 mg/m ³	10 mg/m ³	n/a
Nickel #	(7440-02-0)		1 mg/m ³	1 mg/m ³	n/a
Phosphorus #	(7723-14-0)		0.1 mg/m ³	0.01 mg/m ³	n/a
Selenium	(7782-49-2)		0.2 mg/m ³	0.2 mg/m ³	n/a
Silicon	(7440-21-3)	(Dust)	10 mg/m ³	10 mg/m ³ (1)	n/a
		(Fume)	5 mg/m ³	n/a	n/a
Silver #	(7440-22-4)		0.01 mg/m ³	0.1 mg/m ³	n/a
Sulfur Dioxide	(7446-09-5)		5 mg/m ³	5 mg/m ³	5/10 mg/m ³
Tellurium #	(13494-80-9)		0.1 mg/m ³	0.1 mg/m ³	n/a
Tin (2)	(7440-31-5)		2 mg/m ³	2 mg/m ³	0.2 mg/m ³ (contemporarily)
Titanium Dioxide	(13463-67-7)	(Dust)	15 mg/m ³	10 mg/m ³	n/a
Zinc #	(1314-13-2)	(Dust) (1)	10 mg/m ³	10 mg/m ³	n/a
		(Fume)	5 mg/m ³	5 mg/m ³	10 mg/m ³
Zirconium	(7440-67-7)		5 mg/m ³	5 mg/m ³	10 mg/m ³

* Ceiling Limit

Note: antimony trioxide, beryllium, cadmium, chromium, cobalt chromium alloy, lead and nickel have been identified as potential human carcinogens, # denotes a toxic chemical or chemicals subject to reporting requirements of Section 131 of Title III of the S.A.R.A of 1986 and CFR Part 372.

(1) Value is for total dust containing no asbestos and less than 1% free silicon

(2) Contemplated change to 0.2 STEL and 0.1 TWA

(3) Under court remand

SECTION III.

PHYSICAL DATA

Physical Form:	Solid	Specific Gravity:	7.45-9.00
Boiling Point:	Not Applicable	Vapor Density:	Not Applicable
Freeze-Melt Temperature:	Approximately 1290 - 2260 degrees F	Solubility in Water:	Insoluble
Vapor Pressure:	Not Applicable	Color:	Silver or Yellow to Red
Evaporation Rate:	Not Applicable	Odor:	None

SECTION IV. FIRE AND EXPLOSION DATA

Flash Point: (Method Used) Not Applicable

Extinguishing Media: See Below

Flammable Limits (LEL-UEL) Not Applicable

Auto Ignition Temp.- Not Applicable

Special Fire Fighting Procedures: Solid massive form is not combustible. Fire and explosion hazards are moderate when material is in the form of dust and exposed to heat, flames, chemical reaction, or in contact with powerful oxidizers. Use special mixtures of dry chemical or sand. Firefighters should wear NIOSH/MSHA self-contained breathing apparatus and protective clothing. Molten metal may react violently with water.

SECTION V. REACTIVITY DATA

Stability : Stable

Conditions to Avoid: Stable under normal conditions of transport and storage. Molten metal may react violently with water.

Incompatibility (Materials to Avoid): Acids, bases, and oxidizers.

Hazardous Decomposition or Byproducts: Metal fume.

Hazardous Polymerization: Will not occur.

SECTION VI. HEALTH HAZARD DATA

Permissible exposure limits and threshold limit values. SEE SECTION II

Route(s) of Entry: Inhalation: Yes Skin: Yes Ingestion: Yes

Under normal handling conditions the solid alloy presents no significant health hazards. Processing of the alloy by dust or fume producing operation (grinding, buffing, heating, welding, etc.) may result in the potential for exposure to airborne metal particulates or fume. The exposure levels in Section II are relevant to fumes and dusts

Effects of Overexposure:

Aluminum- Excessive exposure to aluminum fume and dust has been associated with lung disease, but this effect is probably due to simultaneous silica exposure.

Antimony- Antimony and its compounds are irritating to the skin and mucous membranes and are systemic poisons. Effects are reported to include metallic taste in the mouth, vomiting, colic, loss of appetite and weight, cardiac problems, and diarrhea. In addition, dermatitis may result which starts as an inflammation of the hair follicles and can progress through pus formation and sloughing to leave a contracted scar.

Beryllium- Inhalation of beryllium dust or fume may result in the production of an acute or chronic systemic disease depending upon the level of exposure and the beryllium compound involved. Granulomatous lesions of the skin, liver, kidneys, spleen, and lymph nodes have been reported.

Damage to the lungs may be in both the acute and chronic forms, both of which have similar signs and symptoms. These include relatively non-productive cough, progressive difficulty in breathing, loss of appetite, and loss of weight. The major difference between the two is the suddenness of onset and the rate of progression. In the acute form, the symptoms appear in several hours to several weeks after exposure and there is usually rapid progression of signs including dyspnea, anorexia, and extreme weight loss. Complete recovery is possible and fatal cases usually result from acute heart disease. In chronic beryllium disease, the symptoms or signs are generally delayed in their onset and are persistent in nature. They may be triggered or aggravated by stresses such as pregnancy, respiratory infection, and thyrotoxicosis. In the progression of the disease, symptoms of heart disease may occur.

Beryllium is also a suspected human carcinogen and has caused cancer in laboratory animals.

Cadmium- Inhalation of cadmium fumes may cause respiratory irritation with a sore, dry throat and a metallic taste followed by a cough, chest pain, and difficulty in breathing. Bronchitis, pneumonitis, and pulmonary edema have been reported as a result of the irritation of the fumes. Headaches, dizziness, loss of appetite, and weight loss have also been reported and the liver, kidneys and bone marrow may be injured by the presence of the metal.

Continued exposure to lower levels of cadmium has resulted in chronic poisoning characterized by irreversible lung damage and kidney damage. A single, high level exposure to cadmium can cause severe lung irritation which may be fatal. Cadmium is also a suspected human carcinogen.

Chromium- In some workers, chromium compounds act as allergens and may cause dermatitis and may also produce pulmonary sensitization. Chromic acid and chromates have a direct corrosive effect on the skin and mucous membranes of the upper respiratory tract. Although rare, there may be the possibility of skin and pulmonary sensitization. IARC has determined that there is sufficient evidence of increased lung cancer among workers in the chromate-producing industry and possible chromium alloy workers. This determination is supported by sufficient evidence for carcinogenicity to animals and possible mutagenicity testing of Cr VI compounds.

Cobalt- Cobalt has been reported as causing hypersensitization type dermatitis in individuals who are susceptible. Animal studies have shown that particulate cobalt is an acutely irritating substance and industrial exposures, possibly combined with small amounts of silica, are reported capable of producing serious pneumoconiosis which is initially of an insidious nature.

Copper - Melting, grinding, cutting of copper may produce fumes or dust exposure and breathing these fumes or dust may present potentially significant health hazards. Fumes of copper may cause metal fume fever with flu-like symptoms and skin and hair discoloration. While industrial dermatitis has not been reported, keratinization of the hands and the soles of the feet has been reported. Systemically as well, copper dust and fumes cause irritation of the upper respiratory tract, metallic taste in the mouth, and nausea.

Iron - The inhalation of iron oxide fumes or dust may cause an apparent benign pneumoconiosis which is called siderosis. This disease is reported to be disabling, but makes x-ray diagnosis of other lung conditions difficult or impossible

Lead- Short term exposure: Lead is an accumulative poison. Inhalation effects of exposure to fumes or dust of inorganic lead may not develop quickly. Symptoms may include decreased physical fitness, fatigue, sleep disturbance, headache, aching bones and muscles, constipation, abdominal pains, and decreasing appetite. The effects are reversible and complete recovery is possible. Inhalation of large amounts of lead may lead to seizures, coma and death.

Lead- Long term exposure: Long term exposure can result in a buildup of lead in the body and more severe symptoms. These include anemia, pale skin, a blue line at the gum margin, decreased hand grip strength, abdominal pain, severe constipation, nausea, vomiting, and paralysis of the wrist joint. Prolonged exposure may also result in kidney damage. If the nervous system is affected, usually due to very high exposure, the resulting effects include severe headache, convulsions, coma, delirium, and death. Alcohol ingestion and physical exertion may bring on symptoms. Continued exposure can result in decreased fertility and/or increased chances of miscarriage or birth defects.

Manganese- Chronic manganese poisoning may result from inhalation of dust or fume. The central nervous system is the chief site of the injury, and there also may be adverse blood and kidney effects. Chronic manganese poisoning is not a fatal disease although it is extremely disabling. Some individuals may be hyper susceptible to manganese. Freshly formed manganese fume has caused fever and chills similar to metal fume fever.

Nickel- The most common ailment arising from contact with nickel or its compounds is an allergic dermatitis known as "nickel itch" which usually occurs when the skin is moist. Generally nickel and most salts of nickel do not cause systemic poisoning, but nickel has been identified as a suspected carcinogen. There can also be adverse effects to the lungs and nasal cavities.

Silicon- Accumulation in lungs may be responsible for benign pneumoconiosis, but is not considered to be responsible for pulmonary functional impairment or respiratory symptoms.

Tin- The inhalation of inorganic tin fumes or dust may cause an apparent benign pneumoconiosis called stannosis which is reported to be disabling.

Zinc-(as oxide)- Zinc is very low in toxicity but inhalation of fumes may cause "metal fume fever." Onset of symptoms may be delayed 4-12 hours and include irritation of the nose, mouth and throat, cough, stomach pain, headache, nausea, vomiting, metallic taste, chills, fever, pains in the muscles and joints, thirst, bronchitis or pneumonia and a bluish tint to the skin. These symptoms go away in 24-48 hours and leave no effect.

NOTE: Antimony trioxide, beryllium, cadmium, chromium, cobalt-chromium alloy, lead and nickel have been identified as potential human carcinogens.

EMERGENCY FIRST AID PROCEDURES:

Eye Contact- Flush well with running water to remove particulate. Get medical attention

Skin Contact- Vacuum excess dust. Wash well with soap and water.

Inhalation- Remove to fresh air. Get medical attention

Ingestion- Seek medical attention if large quantities of materials have been ingested.

SECTION VII. PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: No special precautions are necessary for spills of bulk material. If large quantities of dust are spilled, remove by vacuuming or wet sweeping to prevent heavy concentration of airborne dust. If liquids (acids or bases) containing solubilized metal are spilled evacuate unprotected personnel from area. Absorb liquid by means of vermiculite, dry sand or similar material. Follow federal, state, and local regulations concerning the disposal of waste.

Waste Disposal Method: Dispose of in accordance with federal, state and local regulations. Cleanup personnel should wear respirators and protective clothing. Ventilate area of release.

Precautions to be Taken in Handling and Storing: Store material away from incompatible materials and keep dust from sources of ignition.

Other Precautions: See all other sections of this MSDS.

SECTION VIII. CONTROL MEASURES

Respiratory Protection: If exposure above the PEL or TLV, NIOSH/MSHA approved respirator for fume or dust, dependent upon the source of airborne contaminant.

Ventilation: Required if dust or fume created in handling or working on this material.

Local Exhaust: Required if dust or fume created in handling or working on this material and threshold limits are being approached.

Mechanical (general): As above to reduce airborne dust or fume levels.

Protective Gloves: Required for melt, grind, cut or weld operations. Select glove approved for the specific operation.

Eye Protection: Required for melt, grind, cut or weld operations. Minimum requirements of safety glasses with side shields for these operations. Melting and welding may require special eye protection including face shields and specially tinted glass. Grinding operations may also require face shields.

Other Protective Clothing or Equipment: As required for the work done on or with the metal.

Work/Hygiene Practices: As required for the work done with lead bearing materials. Meet requirements of the OSHA lead standard where necessary. Always evaluate the jobs done on this product in accordance with OSHA or relevant state, federal, or local standards.

IMPORTANT

LIABILITY DISCLAIMER

The information contained in this Material Safety Data Sheet (MSDS) is believed to be correct as it was obtained from sources we believe are reliable, including: "Threshold Limit Values & Biological Exposure Indices for 1988-89" (American Conference of Government & Industrial Hygienists), Air Contaminates--Permissible Exposure Limits (Title 29, Code of Federal Regulations, part 1910.1000--OSHA) and OSHA (Cleveland Area Office) letter of 6/15/89. However, no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for particular applications, hazards connected with the use of the material, or the results to be obtained from the use thereof. User assumes all risks and liability of any use, processing or handling of any material, variations in methods, conditions and equipment used to store, handle or process the material and hazards connected with the use of the material are solely the responsibility of the user and remain at his/her sole discretion.

Compliance with all applicable federal, state, and local laws and regulations remains the responsibility of the user, and the user has the responsibility to provide a safe work place, to examine all aspects of its operation and to determine if or where precautions, in addition to those described herein, are required.

Note: The copper and copper alloy products are in solid form and will not result in an environmental exposure in such form. We cannot anticipate all the processes or applications to which this product might be subjected or which might create exposures. The information supplied has been furnished by our suppliers and consequently, our company assumes no responsibility for the accuracy or completeness of the data contained herein.

COPPER/COPPER ALLOY % COMPOSITION

ALLOY	CU	LEAD PB	IRON Fe	TIN Sn	ZINC Zn	PHOS P	ARS As	NICKEL Ni	MAG Mn	ALUM Al	TRACE	SPEC
194 IRON	97.0 MIN	0.03 MAX	2.1 2.6		0.05 0.20	0.015 0.15						
360 FITTING	60.0 63.0	2.5 3.7	0.35 MAX		REM							B16
444 ANT	70.0 73.0	0.07 MAX	0.06 MAX	0.9 1.2	REM		0.02 .1SB					B111
464 NAVAL	59.00 62.00	0.20 MAX	0.15 MAX	0.50 1.00	REM							B21
740 NI AG	69.0 73.5	0.010 MAX	0.25 MAX		REM			9.0 11.0	0.5 MAX			B122
752 NI AG	63.0 66.5	0.05	0.25		REM			16.5 19.5	0.5 MAX			B151
90 - 10 706 - CUNI	REM	0.05 MAX	1.0 1.8		1.0 MAX			9.0 11.0	1.0 MAX			B111
70 - 30 715 - CUNI	MAX	0.05 MAX	0.40 1.0		1.0 MAX			29.0 33.0	1.0 MAX			B111

COPPER/COPPER ALLOY % COMPOSITION

ALLOY	CU	LEAD PB	IRON Fe	TIN Sn	ZINC Zn	PHOS P	ARS As	NICKEL Ni	MAG Mn	ALUM Al	TRACE	SPEC
102 CU	99.95 MIN										REM	
120 CU	99.90 MIN					0.004 0.012						B75
122 CU	99.9 MIN					0.015 0.040						B75
220 BRONZE	89.0 91.0	0.05 MAX	0.05 MAX		REM							
230-85/15	84.0 86.0	0.05 MAX	0.05 MAX		REM							B135
260-70/30	68.5 71.5	0.07 MAX	0.05 MAX		REM							B135
270	63.0 68.5	0.10 MAX	0.07 MAX		REM							B135
272 BRASS	62 65	0.07 MAX	0.07 MAX		REM							B135
330-L/L	65.0 68.0	0.25 0.7	0.07 MAX		REM							B135
332-HI/L	65.0 68.0	1.5 2.5	0.07 MAX		REM							B135
443-ARS	70.0 73.0	0.07 MAX	0.06 MAX	0.9 1.2	REM		0.02 0.06					B111